

Safety Data Sheet



Air Tool Oil

AES-820, AES-822, AES-824

Section 1. Identification

GHS product identifier	Air Tool Oil
Stock Number	AES-820, AES-822, AES-824
Chemical name	Distillates (petroleum), hydrotreated light paraffinic
Other means of identification	Baseoil – unspecified; Distillates, petroleum, hydrotreated light paraffinic; Mineral oil, petroleum distillates, hydrotreated light paraffinic; Mineral oil, petroleum distillates, hydrotreated (mild) light paraffinic; Distillates (petroleum), hydro-treated light paraffinic; Base oil – unspecified; Paraffin oil
Product type	Liquid

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial applications: Air tool mechanism lubrication

Uses advised against

Not available.

Reason

Supplier's details

A to Z Products Co., Inc.
2008 National Guard Drive
Plant City, FL 33563 USA
Support: 800-237-1264

Emergency telephone number (with hours of operation)

24 hr. CHEMTREC 1-800-424-9300 / International 1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture ASPIRATION HAZARD – Category 1

GHS label elements

Hazard pictograms



Signal word

Danger

Hazard statements

May be fatal if swallowed and enters airways.

Precautionary statements

Prevention

Not applicable.

Response

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

None known.

Section 3. Composite/information on ingredients

Substance/mixture Substance

Air Tool Oil

Section 3. Composite/information on ingredients

Chemical name	Distillates (petroleum), hydrotreated light paraffinic
Other means of identification	Baseoil – unspecified; Distillates, petroleum, hydrotreated light paraffinic; Mineral oil, petroleum distillates, hydrotreated light paraffinic; Mineral oil, petroleum distillates, hydrotreated (mild) light paraffinic; Distillates (petroleum), hydro-treated light paraffinic; Base oil – unspecified; Paraffin oil
CAS Number/other identifiers	
CAS number	64742-55-8

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light paraffinic	100	64742-55-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or environmental and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye Contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin Contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	No specific data.
Ingestion	Adverse symptoms may include the following: nausea or vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physicians	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Air Tool Oil

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire. Do not use water jet.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	No specific data.
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Air Tool Oil

Section 8. Exposure controls/personal protection

Chemical name Distillates (petroleum), hydrotreated light paraffinic

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic	ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours.

Appropriate engineering controls Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side shields.

Skin protection

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	Liquid. [Viscous liquid.]
Color	Colorless to light yellow.
Odor	Hydrocarbon
Odor threshold	Not available.
pH	Not available.
Melting point	0°C (32°F)
Boiling point	207 to 750°C (404.6 to 1382°F)
Flash point	Open cup: 191°C (375.8°F) [Cleveland.]
Evaporation rate	<0.038 (butyl acetate =1)
Flammability (solid, gas)	Not available.
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	0.00013 kPa (0.001 mm Hg) [room temperature]

Air Tool Oil

Section 9. Physical and chemical properties

Vapor density	Not available.
Relative density	0.852
Solubility	Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/water	>6
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic (40°C (104°F)): 0.141 cm ² /s (14.1 cSt)

Section 10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rate	>5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Conclusion/summary

The classification as a carcinogen need not apply as it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Air Tool Oil

Section 11. Toxicological information

Aspiration hazard

Product/ingredient name	Exposure
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD – Category 1

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye Contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	No specific data.
Ingestion	Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Potential chronic health effects

General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light paraffinic	Acute EC50>100mg/l	Algae	72 hours
	Acute EC50>100mg/l	Daphnia	48 hours
	Acute LC50>100mg/l	Fish	96 hours

Air Tool Oil

Section 12. Ecological information

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated light paraffinic	-	-	Inherent

Bio accumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated light paraffinic	>6	-	high

Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification Not regulated.

Section 14. Transport information

UN number	DOT Classification	TDG Classification	IMDG	IATA
	Not regulated.	Not regulated.	Not regulated.	Not regulated.

Special precautions for user Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II or MARPOL 73/78 and the IBC Code Not available.

Section 15. Regulatory information

U.S. Federal regulations TSCA 8(a) CDR Exempt/Partial exemption: This material is listed or exempted.

Clean Air Act Section 112 Not listed.

Clean Air Act Section 602 Class I Substances Not listed.

Clean Air Act Section 602 Class II Substances Not listed.

DEA List I Chemicals (Precursor Chemicals) Not listed.

DEA List II Chemicals (Essential Chemicals) Not listed.

SARA 302/304

Composition/information on ingredients

No Products were found.

SARA 304 RQ Not applicable.

Air Tool Oil

Section 15. Regulatory information

SARA 311/312

Classification Not applicable.

Composition/information on ingredients

No Products were found.

State regulations

Massachusetts This material is listed.
New York This material is not listed.
New Jersey This material is listed.
Pennsylvania This material is not listed.

California Prop. 65

This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International lists

National inventory

Australia This material is listed or exempted.
Canada This material is listed or exempted.
China This material is listed or exempted.
Europe This material is listed or exempted.
Japan This material is listed or exempted.
Malaysia Not determined.
New Zealand This material is listed or exempted.
Philippines This material is listed or exempted.
Republic of Korea This material is listed or exempted.
Taiwan This material is listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
Asp. Tox. 1, H304	Expert judgement

History

Date of issue/Date of revision 07/01/2015
Version 1.0

Key to abbreviations

ATE = Acute Toxicity Estimate
BCF = Bio concentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
("MARPOL" = marine pollution)
UN = United Nations

Notice to reader

To the best of our knowledge the Information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.